

AUX205N Network Waterproof Column Speaker

Features



- Full-range frequency speaker, clear bass and treble.
- 10 / 100M adaptive, support DHCP / static IP, support LAN and WAN.
- It is able to operate independently from the network and the host.
- The design is overall waterproof with the IP66 test. Aluminum alloy box, it is not easy to have deformation and rust.

Description

AUX205N is waterproof with built-in memory, especially produced for DSP9000 Network Audio System, which is easy to set up (no need of IP address setting), easy to use (plug and play), more reliable (support online and offline running). The system includes all kinds of IP terminals like IP Network Server, IP Paging Microphone, IP Speaker, IP Audio Terminal, IP amplifier, IP Fire Alarm Panel, etc. It offers a new IP audio solution to medium to large audio projects such as hotel, supermarket, shopping mall, rest home, school, etc.

Specification

Item		Specification	AUX205N	AUX405N
Acoustic system		Speaker unit	4 " ×2 , 2.5 ×1	4 " ×4 , 2.5 ×1
		Sensitivity (1m,1W)	89±2dB	89±2dB
		SPL (1m)	102±2dB	102±2dB
		Frequency response	140Hz-14KHz	140Hz-14KHz
		Rated power (RMS)	20W	40W
Amp system	Amplifier	Frequency response	20Hz-20KHz	20Hz-20KHz
		S/N ratio	≥81dB	≥81dB
		Distortion	≤0.1%	≤0.1%
	Audio	Decoding format	MP3、WMA、WAV、ACC、OGG、APE、FLAC etc	
Others		Network interface	R J45 (10/100M)	
		Support protocol	TCP/IP、UDP、ICMP、IGMP (Multicast)	
		Power supply	~90-240V	
		Dimension (H×W×D)	400×160×120mm	610×160×120mm
		Weight	5.5kg	6.2kg